


## Technical Data Sheet

ANRIN DRAIN Reinforced Edge Channels KE-150-150S  
with **Stainless Steel Edge Rail** (Loading Class A15 to E600)



## Channel Dimensions



## Material Properties

### Channel Body

- Polymer concrete with polyester resin
- Compression resistance: > 90 N/mm<sup>2</sup>
- Flexural strength: > 22 N/mm<sup>2</sup>
- Water absorption: < 0.05%
- Density: 2.1 - 2.3 kg/dm<sup>3</sup>
- Modulus of elasticity: 25 - 35 kN/mm<sup>2</sup>
- Water penetration level: 0 mm
- Material structure: Capillary free

### Edge Rail

- Stainless steel, factory-installed
- Profile thickness 6 mm

### Grating

- Galvanized steel
- 304 Stainless steel
- Ductile iron
- Iron Age Patterned Profiles
- Custom grates available upon request

## Description and Sizes

- Designed in accordance with DIN 19580 / EN 1433.
- Drainage channel made of polymer concrete.
- Integrated stainless steel edge rails.
- UNILINK joint system, elements of equal installation heights can be joined in any direction.
- For installation of ANRIN DRAIN KE-150 gratings with SnapLock fastening.
- Fall type: No Slope
- Loading classes: A 15 to E 600
- Total height: 130 mm
- Total width: 214 mm
- Length: 1000 mm

## Channel Parts List

Designation	Article	Slope %	Length mm (in)	Width mm (in)	Height mm (in)	Weight kg (lbs.)
KE-150-0150SP*	01414000	0	1000 (39.37)	214 (8.43)	130 (5.12)	20.1 (44.31)
KE-150-0150SPR***	01414050	0	1000 (39.37)	214 (8.43)	130 (5.12)	20.1 (44.31)

\* Channel with mouldings for vertical outlet DA/OD 110

\*\*\* Channel with vertical pipe socket DA/OD 110

Every reasonable effort has been taken to ensure the accuracy of this document. However, we cannot accept responsibility for inaccuracies resulting from undetected errors or omissions.

Toll Free: 877-385-5130  
www.northstarindustries.ca